



KEYS
 J1-6
 J2-6
 J3-3
 J4-4
 J5-4
 J6-3
 J7-3
 J8-4B

CUT & STRAP 4	CUT & STRAP 3	CUT & STRAP 2	CUT & STRAP 1	AS SHOWN
TMS 2532 OR (A) 0000-07FF 2332	2316(A) 0000-07FF TMS 2532 OR (B) 0800-17FF 2332	B2716(A) 0000-07FF B2716(B) 0800-07FF B2716(C) 1000-17FF	TMS 2716(A) 0000-07FF TMS 2716(B) 0800-07FF TMS 2716(C) 1000-17FF	2316E (A) 0000-07FF 2316E (B) 0800-07FF 2316E (C) 1000-17FF RAM BC00-BCFF 6810 B000-B07F B255 A 04 B 05 C 06 CONT. 07 CTC CH1 08 CH2 09 CH3 0A CH4 0B

Rev 3
 To drive 7 digit displays, add a wire from U22 pin 2 to J4 pin 9
 To improve switch inputs,
 Change 6.8K to 470, resistor close to U23
 Change 10K to 1K, resistor close to U22

REVISION	DATE	CHANGE	BY

Use On
 PARTS MUST BE CLEAN AND FREE OF BURRS
 DATE: 10-28-79
 DRAWN: [Signature]
 CHECKED: [Signature]
 APPROVED: [Signature]
 1616 W. Fullerton Ave
 Addison, ILL. 60101
 02-10017D
 MPU2 SCHEMATIC

REV	DESCRIPTION	DATE
2	ADDED RESET PARTS	10-28-79
A	220P RELOCATED, U3 PIN 1 TO PIN 2	9-2-79